

SILICONE SPRAY LUBRICANT PART NO. 52115

PHYSICAL PROPERTIES

Chemical Type.....	Silicone
Appearance.....	Dries clear
Odor.....	Mild
Boiling/Cond. Point.....	-44°F to 290°F
Evaporation Rate.....	Slower than ether
NFPA Flammability Rating.....	2



DESCRIPTION

Dynatex® Silicone Spray Lubricant is a dry film lubricant which waterproofs, protects, reduces corrosion and lubricates. It is colorless, non-toxic, non-staining, non-corrosive and suitable for metal, plastic, rubber, vinyl, leather and wood. Active ingredients comply with FDA and USDA regulations.

FEATURES

- Lubricates to reduce friction and eliminate squeaks in all types of mechanical mechanisms
- Repels water
- Easy application, aerosol spray for maximum coverage, extension tube for hard to reach areas
- Prevents bonding, sticking and deterioration

TYPICAL APPLICATIONS

- Windshield wiper linkage
- Interior hinges, slides or springs
- Snow blower chutes
- Lubricates door locks, trunk lids, brake cables and rubber molding

DIRECTIONS FOR USE

1. Remove dirt and grease from surface being treated.
2. Provide adequate ventilation.
3. Shake can thoroughly before use. Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
4. Holding can 8 to 10 inches from the surface for open area lubrication, or 5 inches using the extension tube provided for hard to reach areas, press the nozzle and discharge the product on the assembly.
5. Wipe excess with cloth.

GENERAL INFORMATION

***Dynatex® Silicone Spray Lubricant* is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.**

STORAGE AND SHELF LIFE

***Dynatex® Silicone Spray Lubricant* should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse of storage building. *Dynatex® Silicone Spray Lubricant* has a shelf life of 18 months from date of shipment**

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 120°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

TRANSPORTATION INFORMATION

DOT Road Shipment Information

DOT Description Consumer Commodity ORM-D

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The user's exclusive remedy and the supplier's sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.

Dynatex® A division of Accumetric, LLC

Dynatex

350 Ring Road
Elizabethtown
Kentucky 42701 USA
(800) 999-2937
TEL (270) 769-5557
FAX (270) 769-6418

Outside U.S.

TEL +1(270) 769-5557
FAX +1(270) 769-6418

Accumetric Asia Pacific, LTD

18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662) 634-3060
FAX (662) 634-3066

Email: sales@dynatexinc.com
Website: www.dynatexinc.com