

### ELECTRICAL PARTS CLEANER PART NO. 52145

#### PHYSICAL PROPERTIES

Physical State.....	Aerosol liquid
Color/Appearance .....	Clear, colorless
Odor.....	Ether-likier
Specific Gravity.....	1.6
Boiling/Cond. Point .....	250 <sup>0</sup> F (121 <sup>0</sup> C)
Solubility.....	0.015% @ 25 <sup>0</sup> C
Evaporation Rate.....	0.09 (BuAc=1)
VOC % .....	Exempt
NFPA Flammability Rating.....	0
pH.....	6.8 – 8.4

#### DESCRIPTION

**Dynatex® Electrical Parts Cleaner** quickly dissolves and flushes away grease, oil and dirt while leaving no residue. Formulated for removing oil, grease, brake fluids, oxidized oils (gum) and asphalt from all types automotive parts and brakes. **Dynatex® Electrical Parts Cleaner** penetrates through dirt and corrosion and flushes them away, eliminating the need to disassemble. It leaves no residue, dries fast and is non-corrosive to metals. **Not safe for use on rubber or plastic parts.**

#### FEATURES

- Instantly cleans electrical parts
- Dries fast with no residue
- Eliminates dismantling

#### TYPICAL APPLICATIONS

- Air conditioning equipment
- Electrical motors
- Alternators
- Starting motors
- Cables
- Regulators
- Air compressors
- Battery chargers
- Portable tools, welders and more...



#### DIRECTIONS FOR USE:

1. Provide adequate ventilation.
2. Protect painted surfaces from over-spray.
3. Shake can thoroughly before use.  
Note: There is no ball agitator inside the can. For best results, aerosol can should be at room temperature before spraying.
4. Holding can 8 to 10 inches from the surface for open area cleaning, or using the extension tube provided for hard to reach areas, press the nozzle and discharge the product on the assembly.

## GENERAL INFORMATION

This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet.

## STORAGE AND SHELF LIFE

*Dynatex® Electrical Parts Cleaner* should ideally be stored in a cool, dry location in unopened containers at a temperature between 46°F (8°C) to 82°F (28°C) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse of storage building. Store in accordance with NFPA 30B for level 1 aerosols. *Dynatex® Electrical Parts Cleaner* has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122°F (50°C). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

## TRANSPORTATION INFORMATION

### DOT Road Shipment Information

DOT Classification ..... Hazardous  
DOT Description Consumer Commodity ORM-D  
UN Number ..... UN1950  
Hazard Class ..... 2.2

## USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used require government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

The supplier warrants only that its products will meet its specifications. There is no use, nor any other express or implied warranty. The user's exclusive remedy and the supplier's sole liability is limited to refund of the purchase price or replacement of any product when to be otherwise than as warranted. The supplier will not be liable for incidental or consequential damages of any kind.

Suggestions of uses should not be taken as inducements to infringe any patents.



**Dynatex**  
350 Ring Road  
Elizabethtown  
Kentucky 42701 USA  
(800) 999-2937  
TEL (270) 769-5557  
FAX (270) 769-6418  
*Outside U.S.*  
TEL +1(270) 769-5557  
FAX +1(270) 769-6418

**Accumetric Asia Pacific, LTD**  
18 Kitpanit Bldg. 5<sup>th</sup> Floor  
#502 Patpong Road  
Suriyawong, Bangrak  
Bangkok, 10500 Thailand  
TEL (662) 634-3060  
FAX (662) 634-3066

Email: [sales@dynatexinc.com](mailto:sales@dynatexinc.com)  
Website: [www.dynatexinc.com](http://www.dynatexinc.com)