

BELT DRESSING PART NO. 52188

PHYSICAL PROPERTIES

Physical State	Aerosol
Color/Appearance	White foamy
Odor	Mild odor
Specific Gravity	0.95
Boiling/Cond. Point	Not established
Solubility	Soluble in water
Evaporation Rate	<1.00 (BuAc=1)
VOC %	15.23%
Vapor Pressure	Not applicable (Propellant)
NFPA Flammability Rating.....	1

DESCRIPTION

Dynatex® Belt Dressing extends belt life by conditioning against drying and cracking. Stops squeal and protects against belt slippage due to heat, cold, dampness, dust and glazing.

Dynatex® Belt Dressing penetrates the cord fibers to restore pliability and flexibility. Recommended for use on all types of machinery and equipment with motor driven belts.

FEATURES

- Provides better grip and traction
- Stops belts from slipping and squealing
- Helps prevent premature wear, drying and cracking
- Easy application, aerosol spray for maximum coverage, extension tube for hard to reach areas
- Protects belts from deterioration due to oxidation and heat
- Tested in accordance to 75/324/EEC Directive 6.1

TYPICAL APPLICATIONS

- Industrial belt drives
- V-belts or flat belts of rubber, leather or fabric
- Automotive
- Farm equipment

Note: Not recommended for use on serpentine belts



DIRECTIONS FOR USE:

1. Provide adequate ventilation.
2. Shake can thoroughly before each use.
3. Belt should be clean and dry.
4. Stop engine before use.
5. Spray a thin coating on the pulley side of the belt.
6. Idle engine for a short period of time to run belt and evenly distribute coating.
7. Treatment may be repeated when belt squeals or slips.

Note: Prolonged or recurring squeaking is an indication that the belt should be replaced due to excessive wear and deterioration.

GENERAL INFORMATION

This product is not recommended for use in pure oxygen environments and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet.

STORAGE AND SHELF LIFE

Dynatex[®] Belt Dressing should ideally be stored in a cool, dry location in unopened containers at a temperature between 46^oF (8^oC) to 82^oF (28^oC) unless otherwise labeled. DO NOT store within 1 meter (4 feet) of roofline of the warehouse or storage building. Store in accordance with NFPA 30B for level 1 aerosols.

Dynatex[®] Belt Dressing has a shelf life of 18 months from date of shipment

Contents under pressure. Do not smoke while using or use near open flame. Container may explode if heated in any manner. Protect from sunlight and do not expose to temperatures exceeding 122^oF (50^oC). Do not pierce or burn container, even after use. Do not spray on a naked flame and any incandescent material. **DO NOT SMOKE WHILE USING THIS PRODUCT.**

TRANSPORTATION INFORMATION

DOT Road Shipment Information

DOT Classification Hazardous
DOT Description Consumer Commodity ORM-D
UN Number UN1950
Hazard Class 2
Packing Group N/A

USERS PLEASE READ

The information and data contained herein is believed to be accurate and reliable; however, it is the user's responsibility to determine suitability of use. Since the supplier cannot know all the uses, or the conditions of use to which these products may be exposed, no warranties concerning the fitness or suitability for a particular use or purpose are made.

It is the user's responsibility to thoroughly test any proposed use of our products and independently conclude satisfactory performance in the application.

Likewise, if the application, product specifications or manner in which our products are used requires government approval or clearance, it is the sole responsibility of the user to obtain sure authorization.

Non-warranty: Because the storage, handling and application of the material is beyond Dynatex control, we can accept no liability for the results obtained. Dynatex sole limited warranty is the product meets the manufacturing specifications in effect at time of shipment. There is no warranty of merchantability or fitness for use, nor any other express or implied warranty. Dynatex will not be liable for incidental or consequential damages of any kind. The exclusive remedy for breach of such limited warranty is a refund of purchase price or replacement of any product shown to be other than as warranted.

Suggestions of uses should not be taken as inducements to infringe any patents.



Dynatex
350 Ring Road
Elizabethtown
Kentucky 42701 USA
(800) 999-2937
TEL (270) 769-5557
FAX (270) 769-6418
Outside U.S.
TEL +1(270) 769-5557
FAX +1(270) 769-6418

Accumetric Asia Pacific, LTD
18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
TEL (662) 634-3060
FAX (662) 634-3066

Email: sales@dynatexinc.com
Website: www.dynatexinc.com