



Safety Data Sheet

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
System Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 1 - Chemical Product and Company Identification

Product Name: VP Diesel All in One

VP Racing Fuels, Inc., 7124 Richter Road, Elmhurst, TX 78112, 210.635.7744

Recommended Use: Fuel system treatment

RESTRICTIONS on USE

THIS STABILIZER

IS FOR

DIESEL ENGINES ONLY

Emergency Response Number: CHEMTREC 800-424-9300

International Emergency Telephone Number: 703-527-3887

Section 2 - Hazards Identification

GHS HAZARD

Hazard Classes

Flammable liquid/vapor
Eye Irritation
Skin Irritation
Specific Target Organs toxicity single exposure
Specific Target Organs repeated exposure
Acute Toxicity (Oral)
Acute Toxicity (Inhalation)
Reproductive Toxicity
Carcinogenicity Toxicity
Acute Toxicity (Dermal)

Hazard Categories

Category 4
Category 2A
Category 2
Category 3
Category 2
Category 4
Category 3
Category 1B
Category 2
Category 4

Signal Word: Danger

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
System Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act



Toxic

Irritant

Health

Pictograms:

Hazard Statements

PHYSICAL HAZARDS:

H227: Combustible liquid and vapor

HEALTH HAZARDS:

H301: Toxic if swallowed
H315: Causes skin irritation
H312: Harmful in contact with skin
H319: Causes serious eye irritation
H331: Toxic if inhaled
H351: Suspected of causing cancer
H361: Suspected of damaging fertility or the unborn child
H336: May cause drowsiness or dizziness
H372: May cause damage to organs

ENVIRONMENTAL HAZARDS:

None

PRECAUTIONARY STATEMENTS:

P102: Keep out of reach of children
P202: Do not handle until all safety precautions have been read and understood
P210: Keep away from sparks and open flames- No smoking
P260: Do not breathe vapors
P280: Wear protective gloves, clothing and eye protection

RESPONSE STATEMENTS:

P301 +310+ P331: IF SWALLOWED: USA Immediately call the National POISON CENTER at 800-222-1222. OUTSIDE USA Immediately call poison center or doctor. DO NOT induce vomiting
P303+P361+353: IF ON SKIN Take off immediately all contaminated clothing. Rinse skin with water
P304+340: IF INHALED, Remove to fresh air and keep comfortable for breathing
P305+P351: IF IN EYES rinse cautiously with water for at least 15 minutes
P306+P361: IF ON CLOTHING, Take off contaminated clothing
P370: In case of fire use foam, carbon dioxide, dry chemical to extinguish fire
P376: Stop leaks if safe to do so. See section 6 for proper clean up

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

STORAGE STATEMENTS: P403: Keep Cool Store in a well-ventilated place

DISPOSAL STATEMENTS: P501: Dispose of content and/or container in accordance with local, regional, national or international regulations

Section 3 - Composition / Information on Ingredients

CAS#	EC#	Chemical Names	Percent	Other Identifiers
Proprietary	Proprietary	Component A	90%	Component A
Proprietary	Proprietary	Component B	5%	Component B
Proprietary	Proprietary	Component C	2%	Component C
Proprietary	Proprietary	Component D	2%	Component D
Proprietary	Proprietary	Component E	.80%	Component E
Proprietary	Proprietary	Component F	0.2%	Component F

Trade Secret Provision and Chemical Concentration Disclosure: In accordance with OSHA and GHS Regulations we have withheld specific chemical identities. The chemical concentrations have been disclosed as a range and are applicable to the hazards as identified in this Safety Data Sheet.

Section 4 - First Aid Measures

Eye: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin: Prolonged and repeated liquid contact can cause defatting and drying of the skin and can lead to irritation and/or dermatitis.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

Ingestion: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

Inhalation: Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and IF TRAINED, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

After first aid, get appropriate paramedic, or community medical support. The severity of outcome following ingestion may be more related to the time between ingestion and treatment, rather than the amount ingested. Therefore, there is a need for rapid treatment of any ingestion exposure.

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or 703-527-3887 . We will require a written statement of need and confidentiality agreement, in accordance with OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

General Fire Hazards

Use water to cool containers exposed to fire

Hazardous Combustion Products

Avoid fumes of burning product.

Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog

Fire Fighting Equipment/Instructions Large fires evacuate area and fight fire from a safe distance or protected location. Approach fire from upwind to avoid exposure to this material and its toxic decomposition products. Wear full protective gear if exposure is possible.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Ventilate area. Wear adequate protective equipment. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.

Spills: Avoid direct contact with material. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

Handling Precautions: Keep away from ignition sources such as heat, sparks and open flames NO SMOKING Take precautionary measures against static discharge. Non sparking tools should be used. Wear protective gloves, clothing and eye protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment. Empty containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death.

Storage Requirements: Store in original manufacture container tightly closed container in a cool, dry and well-ventilated area.

Chemical Incompatibilities: Strong oxidizing agents and strong reducing agents.

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 8 - Exposure Controls / Personal Protection

Chemical Names	ACGIH- TLV	OSHA - PEL
Component A	25 ppm	*50 ppm
Component B	20 ppm	*200 ppm
Component C	Not Established	Not Established
Component D	10 ppm	10 ppm
Component E	2 mg/m3	*10 mg/m3
Component F	Not Established	Not Established

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value.
OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits.

NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded."

Note: Toluene 500 ppm ceiling concentration.

Note: California PEL for Toluene 10ppm

*Listed on the OSHA Z1 and Z 2 Tables

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Contaminated Equipment: Separate contaminated work clothes from street clothes and launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Personal protective equipment

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the **ANSI/ISEA 105-2011** or European EN374 Standard.

Full contact: Nitrile rubber

Splash contact: Nitrile rubber

This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use. It should not be construed as offering an approval for any specific use scenario.

Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection

Impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
 Conforms to The United Nations Regulation Globally Harmonized System
 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
 Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
 Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Protective Clothing Pictograms



Splash Goggles



Gloves



Protective Apron



Vapor Respirator

A respirator is not needed under normal conditions of product use

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance: Yellow

Odor: Petroleum solvent order

Vapor Pressure: 329.9 mmHg@21°C

Vapor Density (Air=1): .4.1

Specific Gravity (H2O=1,): 0.90 @ 68°F / 20°C

pH: None

Water Solubility: Soluble

Flash Point: 154°F (68°C) closed cup

Boiling Point: 366°F (169°C)

Lower Explosive Limits (vol % in air): 1%

Upper Explosive Limits (vol % in air): 10%

Melting Point: 103°F (75°C)

Viscosity: 3.26 mPa.s at 20 deg C

Auto ignition Temperature: Not Available

Section 10 - Stability and Reactivity

Stability: Stable under ordinary conditions of use and storage.

Polymerization: Hazardous polymerization has not been reported.

Chemical Incompatibilities: Strong oxidizing agents and Perchloric Acid

Hazardous Decomposition Products: Peroxides

Conditions to Avoid: Temperatures above 62°C, heat, sparks, open flames, other ignition sources.

Corrosivity to Metals: Attacks some stainless steels, Light metals giving off hydrogen

Corrosivity to Non-Metals: Attacks some plastics, like chlorinated polyvinyl chloride (CPVC), polyvinyl chloride (PVC), polyethylene terephthalate, high-density polyethylene, and ethylene vinyl acetate; elastomers, like Viton (FKM), nitrile Buna-N (NBR), chloroprene, isoprene, natural rubber, polymethacrylate (acrylic) and silicone; and coatings, such as coal tar epoxy, epoxy general purpose and epoxy chemical resistant.

Section 11- Toxicological Information

Product Name	Results	Species	Dose	Exposure
Component A	Oral LD50	Rat	530 mg/kg	4 hours
Component A	Inhalation LC50	Rat	925 ppm	4 hours
Component A	Dermal LC50	Rabbit	500 mg/kg	Non Listed
Component B	Oral LD50	Rat	>870 mg/kg	4 hours
Component C	Oral LD50	Rat	>5,000 mg/kg	Non Listed
Component D	Oral LD50	Rat	2,900 mg/kg	Non Listed
Component D	Inhalation LC50	Rat	15.8mg/l	4 hours

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
 Conforms to The United Nations Regulation Globally Harmonized System
 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
 Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
 Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Component D	Dermal LC50	Rabbit	2,335 mg/kg	Non Listed
Component E	Oral LD50	Rat	890.0 mg/kg	Non Listed
Component F	Oral LD50	Rat	675 mg/kg	Non Listed
Component F	Inhalation LC50	Rat	1.7 mg/l	1 hour
Component F	Dermal LC50	Rabbit	>4,000 mg/kg	Non Listed

The calculated Acute Toxicity Estimate Value (ATE) for this mixture is:

ATE oral = 567 mg/kg

ATE dermal = 562 mg/kg

ATE inhalation (vapours) = 4.35 mg/l

Route of Entry: Inhalation, Ingestion, Absorption, Skin and/or Eye Contact

Aspiration Hazard: None

Inhalation Hazard: Toxic if inhaled

Ingestion Hazard: Toxic if swallowed

Skin Corrosion/Irritation: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Serious Eye Damage/Irritation: Causes serious eye irritation

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness and dizziness. **Specific Target**

Organ Toxicity (Repeated Exposure): Contains material which may cause damage to the following organs
 Blood, Kidneys, Liver, Eyes, Cardiovascular system and Central nervous system (i.e. brain, spinal cord).

Signs and Symptoms: Effects of overexposure can include cause headache, nausea, dizziness, vomiting, drowsiness, incoordination and confusion. Symptoms may be delayed.

Carcinogenicity:

Chemical Name	IARC	ACGIH	NTP	OSHA
Component A	3 not classifiable as a carcinogenicity to humans	A3 - Confirmed animal with unknown relevance to humans	Not listed	Not Listed
Component B	3 not classifiable as carcinogenicity to humans	A4 Not classifiable as a human carcinogen	Not listed	Not listed
Component C	Not listed	Not Listed	Not listed	Not Listed
Component D	2B Indicates the substance is possibly carcinogenic to humans	A3 - Confirmed animal (with unknown relevance to humans	Not listed	Yes
Component E	Not listed	Not Listed	Not listed	Not Listed
Component F	Not listed	Not listed	Not listed	Not listed

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 12 - Ecological Information

Product Name	Results	Species	Exposure
Component A	LC220 mg/l	Fish	96 hours
Component A	EC50 1,815 mg/l.	Daphnia	24 hours
Component A	LC50 900 mg/l	Algae	72 hours
Component B	LC50 7.63 mg/l	Fish	96 hours
Component B	LC50 245.00mg/l	Algae	24 hours
Component B	LC50 4 mg/l	Daphnia	24 hours
Component C	LC50 >100 mg/L	Fish	96 hours
Component C	EC50 >100 mg/L	Algae	72 hours
Component D	LC50 14 mg/l	Fish	96 hours
Component E	LC50 5.3 mg/l	Fish	48 hours
Component E	EC50 1.44 mg/l	Daphnia	48 hours
Component F	LC50 65 mg/l	Fish	96 hours
Component F	EC50 35.4 mg/l	Daphnia	48 hours
Component F	EC50 32 mg/L	Algae	72 hours

Toxicity: This mixture is regarded as toxic to aquatic organisms and should be prevented from entering a waterway.

Mobility: Floats on water, absorbs into soil and has low mobility.

Persistence/degradability: Oxidizes rapidly by photo-chemical reactions in air.

Bioaccumulation: Has the potential to bioaccumulate.

Section 13 - Disposal Considerations

Disposal: DO NOT REUSE EMPTY CONTAINER! Container should be completely emptied prior to discard. Container with residues should be considered to be hazardous wastes. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Section 14 - Transport Information

Regulatory Information	UN #	Proper Shipping Name	Hazard Class	PG	Label	Additional Information
DOT Classification		Not Regulated				
TDG Classification		Not Regulated				
RID/ARD Classification		Not Regulated				
IMDG Classification		Not Regulated				
ICAO/IATA Classification		Not Regulated				
Australian Classification		Not Regulated				

Section 15 - Regulatory Information

US Regulations:

TSCA: Component A, Component B, Component C, Component D, Component F

CERCLA Hazardous Substances and corresponding RQs: Component B 1000 pounds Component D 5000 pounds

SARA Community Right-to-Know Program: Component B, Component D

Clean Water Act: Component B

Clean Air Act: Component D **OSHA:** All ingredients are listed in 1910.1200

State Regulations

California prop. 65: Component B Reproductive

Chemicals on the following State Right to Know Lists:

Massachusetts: Component A, Component B, Component C, Component D, Component F

New Jersey: Component A, Component B, Component C, Component D, Component F

Pennsylvania: Component A, Component B, Component C, Component D, Component F

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Canadian Regulation:

WHMIS Classification: **Component A**

B3 - Flammable and combustible material - Combustible liquid

D1A - Poisonous and infectious material - immediate and serious effects - Very toxic

D2B - Poisonous and infectious material - Other effects - Toxic



B3 - Combustible Liquid



D1A - Very Toxic



D2B - Toxic

WHMIS Health Effects Criteria Met by this Chemical:

D1A - Acute lethality - very toxic - immediate

D2B - Eye irritation - toxic - other

D2B - Skin irritation - toxic - other

WHMIS Classification: **Component B**

B2 - Flammable and combustible material - Flammable liquid

D2A - Poisonous and infectious material - Other effects - Very toxic

D2B - Poisonous and infectious material - Other effects - Toxic



B2 - Flammable Liquid



D2A - Very Toxic



D2B - Toxic

WHMIS Health Effects Criteria Met by this Chemical:

D2A - Teratogenicity and embryotoxicity - very toxic - other

D2B - Skin irritation - toxic - other

WHMIS Classification: **Component D**

B2 - Flammable and combustible material - Flammable liquid

D1B - Poisonous and infectious material - Immediate and serious effects - Toxic

D2A - Poisonous and infectious material - Other effects - Very toxic

F - Dangerously reactive material



B2 - Flammable Liquid



D1B - Toxic



D2A - Very Toxic



F - Dangerously Reactive

WHMIS Health Effects Criteria Met by this Chemical:

D1B - Acute lethality - toxic - immediate

D2A - Carcinogenicity - very toxic - other

WHMIS Ingredient Disclosure List: Meets criteria for disclosure at 0.1%.

The following substances are specified on the public Portion of the Domestic Substances List (DSL):

Component A, Component B, Component C, Component D, Component G

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Europe Regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC including amendments and take into account the intended product use.

Europe inventory: Component A



EC Symbols

EC Classification: Danger

EC Risk Phrases:

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R36/38: Irritating to eyes and skin.

EC Safety Phrases:

S2: Keep out of the reach of children.

S36/37: Wear suitable protective clothing and gloves.

S46: If swallowed, seek medical advice immediately and show this container or label.

Europe inventory: Component B



EC Symbols

EC Classification: Highly flammable. Harmful

EC Risk Phrases:

R11 Highly flammable.
R38 Irritating to skin.
*R63 Possible risk of harm to the unborn child.
R65 Harmful: may cause lung damage if swallowed.
R67 Vapors may cause drowsiness and dizziness.

EC Safety Phrases:

S2 Keep out of the reach of children.
S23 Do not breathe fumes, vapor or spray.
S24 Avoid contact with skin.
S29 Do not empty into drains.
S36/37 Wear suitable protective clothing and gloves.
S51 Use only in well-ventilated areas.
S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.
S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

VP Diesel All in One

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II – Europe
Conforms to Regulation (EC) No 1272/2008 and aligns to the United Nations Globally Harmonized System
Conforms to the Australian Preparation of Safety Data Sheets for Hazardous Chemicals under section 274 of the Work Health and Safety Act

Europe inventory: Component D



EC Symbols

EC Classification: Highly flammable

EC Risk Phrases:

R11: Highly flammable

EC Safety Phrases:

S2: Keep out of the reach of children

S16: Keep away from sources of ignition - No smoking

S23: Do not breathe vapor

S29: Do not empty into drains

S33: Take precautionary measures against static discharges

International Regulations:

Australian Inventory of Chemical Substance: Component A, Component B, Component C, Component D, Component F

National Existing Chemical Inventory in Taiwan: Component A, Component B, Component C, Component D, Component F

Philippine Inventory of Chemicals and Chemical Substances: Component A, Component B, Component C, Component D, Component F

China Existing Chemical Inventory: Component A, Component B, Component C, Component D, Component F

Section 16 - Other Information

Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

SDS Preparation Date 12/10/2013

SDS Previous issue Date: None

Prepared by SJC Compliance Education, Inc.

16516 El Camino Real suites 417

Houston, TX. 77062